13 Approved For Release 2000/06/09 : CIA-RDP89B00551R000100190013-6

PRE-FLIGHT CHECKLIST FOR PERSONAL EQUIPMENT SECTION

- 1. Pre-Breathing Room (T.O. Minus 2:20);
- a. Orderliness
- b. Security
- c. Utilities (Electricity Air Conditioning)
- 2. Ground Vehicle Check (T.O. Minue 2:20):
- a. Walk Around check
- b. Starting
- c. On Board: Spare Pack (1) Facepiece (1) D-2, 425 psi (2) Cushions (2) Parachutes (2),
- 3. Aircraft Oxygen Check (T.O. Minus 2:20):
 - a. Position Seat Pack in cockpit
 - b. Oxygen pressure 1800 to 2000 psi
 - c. Connect oxygen and check for flow
 - d. Check radio through seat pack
 - e. Check face piece heat on normal and by-pass
 - of. Arrange placement of seat belt, harness, seat pack leads
- 4. Pre-Breathing (T.O. Minus 2:00):
- ✓ a. Oxygen manifold and reduction system "ON"
- b. 150 psi connected to console
- ✓c. Console check flow and pressure 2 to 3 mm Hg
- ✓d. Fit underwear to pilot
- ✓e. Check and fit helmet assembly to pilot
- ✓f. Connect face piece to console turn "ON"
- 5. Check Personal Equipment:
- _a. Suit condition
- b. Helmet
- c. Gloves

Enclosure 2 to SOP-0-1, Page 1

Approved For Release 2000/06/09 : CIA-RDP89R00551R000100190013-6 Boots . /e. Parachute

- Coveralls
- Face piece and carrier
- Store items in sequence of wear after check,
- Periodically insure pilot's oxygen supply adequacy and comfort

6. Clothing Pilot (T.O. Minue:30):

- Ta. Fit Pilot's suit assembly plus coveralls. Check all zippers, lacings and general appearance.
 - →b. Drinking water
- c. Remove pilot from console (Time noted); connect to D-2 charged 425 psi
 - _d. Escort pilot to vehicle and plane

7. At Aircraft (T.O. Minus :20):

- _a. Fit parachute and back pack to pilot
- b. General evaluation of all garments
-c. Pilot hook-up in aircraft: Seat pack hook-up; engage capstan and breathing supply hoses; engage flight face piece to "T" block; connect amphenol; connect "U" plug; oxygen "ON"; check flow and change face piece; shoulder harness and seat belt; face piece heat check; press to test and check inflation.
 - ✓d. Recheck all items get pilots approval
 - Technician and vehicle remain "on line" until aircraft departure.

8. Post Flight:

- a. Report to aircraft at "Switch Off" time.
 - Assist pilot out of aircraft and remove headgear.
 - C. Remove personal equipment from cockpit.
 - Return pilot to operations.
 - Assist in removing clothing.
 - If. Clean and perform minute inspection of all equipment.
 - g. Report to de-briefing for pilot report.